

Aluminum Profiles

i-Modular System, with Partially Closed Slots, Profile Type Light

SPECIFICATION

Profile type

- Type **N**: Light, 2 sides closed, offset by 90°

Aluminum

Anodized, natural color **N**

INFORMATION



Aluminum profiles GN 11i with partially closed slots are produced by extrusion molding. They can be used, for example, to easily construct protective enclosures, workplace equipment or partition walls, when an attractive appearance is required.

Aluminum profiles in combination with the removable and reusable accessories form a flexible modular system. Attachments can be fastened to either the slots or the end faces via the holes.

The closed profile sides facilitate cleaning. The profile type light is typically used for small loads or for weight-optimized constructions. Aluminum profiles are supplied in bundles. The table shows the quantity included in each bundle.

ACCESSORY

- T-Nuts GN 50i (see page)
- Cover Caps GN 60i (see page)
- Cover and Edging Profiles GN 70i (see page)
- Cover Profiles GN 71i (see page)
- Transport and Base Plates GN 80i (see page)



GN 11i

| Description | s1 | s2 | n | Length l in m +1.5mm | Bundle Pieces | d | s3 | t | Grid size | ⚖ |
|---------------------|----|----|---|-------------------------|------------------|-----|-----|-------|--------------|-------|
| GN 11i-40408N-N-2-4 | 40 | 40 | 8 | 2 | 4 | 6.8 | 4.5 | 12.25 | 40 | 14640 |
| GN 11i-40408N-N-3-4 | 40 | 40 | 8 | 3 | 4 | 6.8 | 4.5 | 12.25 | 40 | 21960 |